


AMSLIDE

Slide Way Lube Series

Technical Data Sheet



Smooth Protection



AMSLIDE WAY LUBRICANTS

are Premium quality machine tool slide way lubricants. These products are formulated to prevent stick slip and to resist washout by machine coolants particularly synthetic type water based coolants.

AMSLIDE WAY LUBE meets Cincinnati Milacron P- specifications.

APPLICATIONS

All machine tools requiring slide way lubrication in manual or automatic lubricant applications.

FEATURES & BENEFITS

- Low coefficient of friction prevents stick slip
- Additives to prevent friction and wear
- Contains no chlorinated paraffins
- Low odor and light color

TYPICAL PHYSICAL CHARACTERISTICS

ISO Grade	32	46	68	220
Gravity, ° API	29.9	29.6	29.2	28.1
Density lb./gal.	7.3	7.31	7.34	7.23
Product Shelf Life	12 months			

Viscosity

cSt @ 40° C	32.2	46	66.1	219
cSt @ 100° C	5.3	6.5	8.5	18.6
SSU @ 100° F	166	230	343	997
SSU @ 210° F	44.2	48.1	54.8	89.7
Viscosity Index	97	96	97	96
Pour Point °F	-10	-10	-5	5
Flash Point °F	403	421	432	477

Protect Your Investment.

Chemical Solutions for Today's Challenges

American Research Specialty Products

2535 Palos Verdes Drive West, Suite 208, Palos Verdes, CA 90274

Ph: 310-541-1512 Email: info@americanresearchproducts.com

ISO 9001:2015 certified