

PROTECTSOL 512CA

Water Displacing Thin Film,
Corrosion/Rust Preventive

Product Bulletin



Lasting Protection



PROTECTSOL 512CA

is an oil-based water-displacing corrosion/rust preventive for use on ferrous and non-ferrous metal surfaces. Protectsol 512CA provides up to 6 months indoor storage protection against corrosion & rust with an ease of application. Protectsol 512CA forms a thin, non-staining transparent and highly protective film. Protectsol 512CA will quickly separate alkaline water from metal surfaces.

CLEANABILITY

PROTECTSOL 512CA can be removed with simple alkaline cleaners such as American Research Products AMERICLENE 30MPA.

FEATURES & BENEFITS

- SCAQMD Rule 1144 Compliant
- Meets and exceeds Mil-C-16173 Grade 3 Federal Specification
- Meets and exceeds Mil-C-22235 Federal Specification for corrosion preventive
- De-waters all water miscible solutions such as coolants, cleaners, rinses
- Protectsol 512CA can be used safely on non-ferrous and ferrous metal surfaces

PROPERTIES

Property	Typical value
Odor	Light Solvent
Color	Light Brown Color
Density	6.9 lbs/gal
Specific Gravity	0.84
Flashpoint	212 ^o COC ASTM D92
VOC Content	305 grams/per liter ASTM 1868-10
Product shelf life	1 year

Consult the Safety Data Sheet before using this product for instructions on safe handling and environmental safety. The information contained in this data sheet is accurate to the best knowledge of ARSP Inc. No warranty is expressed or implied regarding the accuracy of this Data Sheet. ARSP Inc. assumes no liability for any alleged damage, or injury resulting from the use of this product unless ARSP Inc. is proven to be solely responsible for any such damage or injury.

Protect Your Investment.

Chemical Solutions for Today's Challenges

American Research Specialty Products

2535 Palos Verdes Drive West, Suite 208, Palos Verdes, CA 90274

Ph: 310-541-1512 Email: info@americanresearchproducts.com

ISO 9001:2000 certified