

AMCUT 7 SLT

Ultra Low VOC Cutting & Grinding Oil

Technical Data Sheet



Premier Performance



AMCUT 7 SLT

is a super light viscosity straight oil for the cutting and grinding of non-ferrous metals. The ultra light viscosity makes it highly effective for use with small parts in vibratory feeders preventing jams. AMCUT 7 SLT contains a highly effective set of additives designed to provide excellent tool and wheel life. This product is Super Compliant with SCAQMD Rule 1144.

FEATURES & BENEFITS

- Ultra Low VOC
- Low Chip Drag Out Rate
- Excellent Tool & Wheel Life
- Superior Oxidation Resistance
- **SCAQMD Super Compliant**
- No SCAQMD Record Keeping Required

PROPERTIES

Property	Typical value
Appearance	Clear Light Yellow
Specific Gravity	.85 -.87
Density	7.4 lbs p. gal
Viscosity @40°C	7 cSt
Viscosity @100°F	30 SUS
Viscosity Index	95
Flashpoint	350°F COC ASTM D92
Copper Strip Corrosion	1A
Chlorine	No
Sulphur	No
Product Shelf Life	12 months

Protect Your Investment.

Chemical Solutions for Today's Challenges

American Research Specialty Products

2535 Palos Verdes Drive West, Suite 208, Palos Verdes, CA 90274

Ph: 310-541-1512 Email: info@americanresearchproducts.com

ISO 9001:2015 certified