CRYO-CUT 909 Heavy Duty Soluble Oil

Technical Data Sheet







CRYO CUT 909

soluble oil is a heavy duty machine coolant. We have combined extreme-pressure ingredients, wetting agents and high lubricity components to achieve outstanding performance with difficult to machine materials in demanding operations. This product is stable in both hard and soft water.

CRYO CUT 909 contains a unique and very effective group of bacteria and fungus preventatives to help control problems caused by growth of bio contaminants. Sump life of the cutting fluid is greatly enhanced and the coolant can remain is service for extended periods.


TYPICAL DILUTION RATIOS

• Heavy turning of difficult alloys	8 to1
 Medium turning, heavy grinding 	12 to 1
 Light cutting, medium alloys 	15 to 1
• Light cutting, high speed, non-ferrous	20 to 1
 O.D., cylindrical grinding 	25 to 1
 Surface, Blanchard Grinding 	30 to 1

PROPERTIES

Property	Typical value
Appearance	Translucent
pH of Concentrate	10.5
pH @ 5%	9.0-9.5
Sp. Gravity	.97
Density	8.05 lbs per gallon
Product Shelf Life	8 months

REFRACTOMETER INDEX:



American Research Specialty Products

2535 Palos Verdes Drive West, Suite 208, Palos Verdes, CA 90274 Ph: 310-541-1512 Email: info@americanresearchproducts.com ISO 9001:2015 certified

Protect Your Investment.

Chemical Solutions for Today's Challenges